

FPD SERIE













Trapano
 Perçeuse
 Drilling machine
 Bohrmaschine
 Taladro
 Furadeira



MOD. FPD60XY



MOD. FPD60

									
	SPESSORI DI VETRO ÉPAISSEURS DE VERRE THICKNESS RANGING GLASSTÄRKEN ESPESESORES DE VIDRIO ESPESSURAS DE VIDRO	Ø MAX DI FORATURA Ø DE PERÇAGE MAX MAX DRILLING Ø MAX BOHRDURCHMESSER Ø MÁX DE PERFORACIÓN Ø MÁXIMO DE FURAÇÃO	VELOCITÀ DEI MANDRINI VITESSE DES BROCHES SPINDLE SPEED SPINDELDREHZAHN VELOCIDAD DE LOS MANDRILES VELOCIDADE DO MANDRIL	ALTEZZA DEL PIANO DI LAVORO HAUTEUR DU PLAN DE TRAVAIL HEIGHT OF WORK SURFACE HÖHE DER ARBEITSFLÄCHE ALTO DEL PLANO DE TRABAJO ALTURA DO PLANO DE TRABALHO	POTENZA INSTALLATA PUISSANCE TOTAL TOTAL CAPACITY STROMBEDARF POTENCIA TOTAL POTÊNCIA TOTAL	PROFONDITÀ DEL BRACCIO PROFONDEUR DU BRAS ARM DEPTH AUSLEGERTIEFE PROFUNDIDAD DEL BRAZO PROFUNDIDADE DO BRAÇO	CONSUMO ARIA CONSUMMATION D'AIR AIR CONSUMPTION LUFTVERBRAUCH CONSUMO DE AIRE CONSUMO DE AR	PESO TOTALE POIDS TOTAL OVERALL WEIGHT GESAMTGEWICHT PESO TOTAL PESO TOTAL	OPZIONALI OPTIONAL ZUBEHÖR OPCIONALES OPÇÕES
FPD60	2/28 mm	3/100 mm automatico 3/200 mm manuale	450/2450 rpm	1.050 mm	KW 2,6	1.100/1.300/1.600 mm	55 NI/min	470 Kg	 
FPD60XY	2/28 mm	3/100 mm automatico 3/200 mm manuale	200/4500 rpm	1.030 mm	KW 4,4	700* mm	50 NI/min	1.372 Kg	 INVERTER

* ≠ a richiesta | ≠ sur demande | ≠ on request | ≠ auf Anfrage | ≠ sobre pedido | ≠ conforme solicitado